

DATASHEET

SKYSAFE PRO FLEX Y



GENERAL

Art.Nr:	L-0733-1,8
GTIN:	4030281265115
E-class number:	40-02-01-04
Customs tariff number:	56090000

Standards:	EN 354:2010, EN 355:2002, EN 795:2012, RFU PPE-R/11.063, RFU PPE-R/11.074
Net weight:	1.26 kg
Gross weight:	1.26 kg

DATASHEET

SKYSAFE PRO FLEX Y

ONE4ALL - The SKYSAFE PRO Revolutionary, new, patented energy absorber with the large weight range from 50 - 140kg (110 - 309 lbs.) that always withstands a maximum impact of less than 6 kN at a maximum absorber length of 1.75m (5.7 Feet). The final impact resistance of 22 kN, also in the absorber, before AND after a fall is exceptional as well. SKYSAFE PRO furthermore meets the most relevant international standards in one SINGLE product. UNIQUE: The built-in, adjustable RESCUE LOOPS! As a result, rescuers need not set up a rescue system and hereby save precious time in a rescue! Available in four versions with different carabiner combinations: I-web, Y-web, I-web tie-back, Y-web tie-back.

FEATURES

Application areas:	Telco energy
Fallindicator:	Yes
Impact force:	6.00 kN
Colour:	Orange, Black, Grey
Hand wash:	40 °C
Edge approved:	Yes
Maximum lifetime:	10 years
Maximum temperature:	45 °C
Minimum tensile strength:	22.00 kN
Minimum temperature:	-35 °C
Rescue loop:	Yes
Lanyard type:	Y-Version

DIMENSIONS

length_lanyard:	1.80 m
Lanyard rope diameter:	30.00 mm

MATERIAL

Material:	Polyester, Aluminium
-----------	----------------------