

DATASHEET

GRYPHON ASCENDER



GENERAL

| | | | |
|------------------------|----------------|---------------|---------------------------------------|
| Art.Nr: | G-1176-S/M | Standards: | EN 358:2018, EN 361:2002, EN 813:2008 |
| GTIN: | 8057733308981 | Net weight: | 2.20 kg |
| E-class number: | 40-21-04-01 | Gross weight: | 2.20 kg |
| Customs tariff number: | 63079098990002 | | |

DATASHEET

GRYPHON ASCENDER

Comfortable and ergonomic harness with six attachment points specifically developed for rope access work and equipped with a triangular quick-link and with CHEST ASCENDER+ ventral rope clamp, for maximum ease of use in rope manoeuvres.

Main features:

- close-fitting construction and wide lumbar support belt with breathable mesh padding for optimal comfort during prolonged suspensions;
- contoured shoulder straps with shape optimized to avoid neck chafing;
- shoulder strap equipped with quick-release buckle;
- leg-loop quick-release buckles with indicator for correct insertion;
- leg-loops designed with targeted panel construction to ensure optimal comfort while in suspension by relieving pressure in the groin area;
- adjustable rear straps that allow the leg loops to be moved along the legs;
- large EN 361 sternal attachment point to facilitate rescue operations;
- EN 358 lateral attachment points with two positions: outward-facing when in use (work mode); inward-folded when not in use (stand-by mode) in order not to hamper the operator's movements;
- EN 361 dorsal attachment point designed to avoid accidentally getting snagged, especially while working in confined spaces;
- attachment point on the rear of the waistbelt, marked by the letter R and exclusively intended for the connection of a restraint lanyard;
- dedicated loop for quick-link, to be used for the addition of a ventral rope clamp in combination with appropriate straps;
- two horizontal straps positioned on the

FEATURES

| | |
|---------------------------------|--|
| Attachment points: | Sternal aluminium attachment point, Dorsal steel attachment point, Side aluminium attachment point, Sit harness aluminium attachment point, Restraint polyester attachment point |
| Number of material loops 10 kg: | 4 |
| Application areas: | Arborists, Rope access, Emergency, Rescue |
| Colour: | Black, Orange |
| Harness features: | Lanyard parking ring, Integrated chest ascender |
| Hand wash: | 40 °C |
| Maximum body height: | 185 cm |
| Maximum lifetime: | 10 years |
| Maximum hip size: | 80 cm |
| Maximum leg size: | 55 cm |
| Maximum temperature: | 60 °C |
| Minimum body height: | 160 cm |
| Minimum hip size: | 60 cm |
| Minimum leg size: | 45 cm |
| Minimum temperature: | -20 °C |
| Padding: | Back padding, Leg paddings, Shoulder paddings |
| Buckles: | stick_buckle, click_buckle |

DATASHEET

GRYPHON ASCENDER

shoulder straps and exclusively intended for the insertion of HOOK REST support;

- two dedicated loops for the connection of a work-positioning seat;
- four large gear-loops, six loops for the tool-holder pouch and four slots for carrying-tools carabiners;
- maximum load: 140 kg.

| | |
|--------------------|---|
| Adjusting buckles: | Adjusting buckles shoulders, Adjusting buckles hips, Adjusting buckles legs |
|--------------------|---|

DIMENSIONS

| | |
|-------|-----|
| Size: | S-M |
|-------|-----|

MATERIAL

| | |
|-----------|--|
| Material: | Polyamide, Polyester, Polyethylene, Steel, Aluminium |
|-----------|--|
