

# DATASHEET

## PEANUT I



### GENERAL

Art.Nr:	HSG-021-2,5-5	Standards:	EN 360:2002,GS-PS-12:2019,RFU PPE-R/11.060:2018,RFU PPE-R/11.085:2020,RFU PPE-R/11.124:2020
GTIN:	4030281181996	Net weight:	2.08 kg
E-class number:	40-02-01-03	Gross weight:	2.08 kg
Customs tariff number:	84798997		

## DATASHEET

### PEANUT I

The compact connecting device PEANUT I with FS92 karabiner convinces with its self-retracting arm, which does not restrict the working radius and ensures that the fall height is extremely low. The karabiner with an opening width of 90 mm is particularly suitable for large structures, such as high shelves or lattice mast structures. The fastener is edge-suitable and thus also serves for horizontal securing. PEANUT I contains the One-4-All damper and is therefore suitable for a very wide range of user weights from 50 to 135 kilograms. The 2.5 m long arm makes PEANUT I ideal for securing in scaffolding. The fastener is available in a variety of karabiner variants (aluminium, steel, etc.). A red indicator shows when the strap has been released and provides additional safety.

#### FEATURES

Application areas:	Scaffolding, Working on masts and towers, Work on roofs and facades
Colour:	Black, Grey, Orange
Edge approved:	No
Maximum user weight vertical:	135.00 kg
Maximum lifetime:	10 years
Maximum number of persons:	1
Maximum temperature:	45 °C
Minimum user weight:	50.00 kg
Minimum temperature:	-35 °C

#### DIMENSIONS

Rope length:	2.50 m
--------------	--------

#### MATERIAL

Material:	Polyester, Polyamide, Steel, Aluminium
-----------	--