

DATASHEET

CRIC



GENERAL

Art.Nr:	H-280	Standards:	EN 12278:2007, EN 12841-B:2006, EN 567:2013
GTIN:	8057733309582	Net weight:	0.14 kg
Customs tariff number:	76169990	Gross weight:	0.14 kg

DATASHEET

CRIC

Multifunctional rope clamp with integrated pulley for rescue and rope access work. Robust, practical and intuitive, it has four different modes of operation: ascender, pulley, rope clamp/pulley or progress-capture hauling pulley.

Main features:

- its versatility, compact size and ease of use allow reducing to the minimum time, material and space needed in rope manoeuvres;
- it allows ascending the rope in accordance with EN 567 / EN 12841-B standards (ascender mode);
- it can be used as a simple pulley for lifting or transferring a load in accordance with the EN 12278 standard (pulley mode);
- the integrated ball-bearing sheave can be used as a simple redirect to make it easier to ascend a rope or to lift a person without the aid of additional connectors (rope clamp/pulley mode);
- it allows the direct lifting of a load, the creation of hauling systems and the rescue or self-rescue of a person (progress-capture hauling pulley mode);
- when used in pulley mode, the rope is free to run in both directions; instead, when the hauling-pulley mode is used, the rope can only run in one direction and it is locked in the opposite one;
- when used in progress-capture hauling pulley mode, it is possible to lower the lifted load by acting on the dedicated cord connected to the cam within the device;
- the easy opening, via an intuitive release button, makes the installation of the device on the rope swift – no matter the mode that is going to be used in – even with gloves on or while operating in difficult conditions;

FEATURES

Application areas:	Arborists, Emergency, Facades cleaning, Tactical approach, Rope access, Rescue, Shaft, Working in confined spaces, High ropes courses
Colour:	Orange, Silver
Maximum lifetime:	12 years
Minimum compatible rope diameter:	8.00 mm
Maximum compatible rope diameter:	11.00 mm
Minimum temperature:	-29 °C
Maximum temperature:	40 °C
Working Load Limit:	100 kg

MATERIAL

Material:	Aluminium, Stainless Steel
-----------	----------------------------

DATASHEET

CRIC

- equipped with a steel cam featuring teeth that minimize rope wear but are effective in blocking the rope. In addition, the cam is designed with two slots to reduce the build-up of dirt, so maintaining the lock on the rope very efficient in any condition (muddy, frozen rope, etc.).