

DATASHEET

XL-D SG



GENERAL

Art.Nr:	H-308-SG	Standards:	EN 12275:2013/B, EN 362:2004/B
GTIN:	8057733305706	Net weight:	0.08 kg
E-class number:	40-21-07-12	Gross weight:	0.08 kg
Customs tariff number:	76169990		

DATASHEET

XL-D SG

Light-alloy hot-forged connector with large capacity base and screwgate, ideal for the connection of multiple devices.

Main features:

- enhanced H-profile, for excellent weight-to-strength ratio;
- wide gate opening and large internal capacity;
- equipped with catch-free closure for effortless clipping;
- compatible with FIX PRO+ positioning device.

FEATURES

Colour:	Orange, Grey, Silver
Swivel:	No
Carabiner properties:	Corrosion resistance
Fallindicator:	No
Gate opening:	29 mm
MBS MAJOR AXIS:	28 kN
MBS GATE OPEN:	10 kN
MBS MINOR AXIS:	12 kN
Form fit:	Key Lock
Carabiner type:	Type B (EN 12275: 2013), Type B (EN 362:2004)
Maximum lifetime:	30 years
Minimum temperature:	-35 °C
Maximum temperature:	45 °C
Standard ANSI:	No
Standard CSA:	No
UIAA compliance:	No
Anti-twist device:	No
Locking mechanism:	Screwgate

MATERIAL

Material:	Aluminium
-----------	-----------

DATASHEET

XL-D SG

