

DATASHEET

MILAN 2.0 POWER



GENERAL

Art.Nr:	A-029
GTIN:	4030281155867
E-class number:	40-21-01-01
Customs tariff number:	84251900

Standards:	ANSI Z359.9-2021, DIN EN 1496-A:2017, DIN EN 341-1A:2011, MEETS CSA Z259. 2.3:16/1/B
Net weight:	3.14 kg
Gross weight:	3.14 kg

DATASHEET

MILAN 2.0 POWER

MILAN 2.0 POWER is THE special version of the MILAN 2.0 HUB. With the RESCUE DEVICE DRIVER (RDD)

https://www.skylotec.com/eu_en/rdd-fur-milan-2-0-power-a-029-g.html it offers an option for fast and safe rescue over long distances upwards. In addition, all manual options for rescue and evacuation are available.

With special SEAL PACs

https://www.skylotec.com/eu_en/seal-pac-set-seal-pac.html an extended lifetime of up to 15 years can be guaranteed, which can even be doubled once within a resealing process to 30 years. Note: When working at heights, a suitable rescue concept based on a risk assessment is essential. MILAN offers a variety of applications for different rescue scenarios. To master these techniques, the user must be carefully trained by a SKYLOTEC-certified instructor who has been specially trained on the device.

FEATURES

Colour:	Black, Orange, White
Lifting function:	Yes
Max. abseiling height:	501 m
Maximum load 1 person:	141.00 kg
Maximum load 2 persons:	280.00 kg
Maximum lifetime:	20 years
Maximum number of persons:	2
Maximum load:	280.00 kg
Minimum compatible rope diameter:	9.00 mm
Maximum compatible rope diameter:	9.00 mm
Max. Abseil speed:	0.90 m/s
Minimum temperature:	-35 °C
Maximum temperature:	60 °C
Panic function:	No
Rescue function:	Yes

MATERIAL

Material:	Aluminium, Steel, Polyamide
-----------	-----------------------------