

DATASHEET

SNAPPY STEEL SG



GENERAL

Art.Nr:	H-291-SG	Standards:	EN 12275:2013/H, EN 362:2004/B, UIAA 121
GTIN:	8056734831702	Net weight:	0.24 kg
E-class number:	40-21-07-12	Gross weight:	0.24 kg
Customs tariff number:	73269098		

DATASHEET

SNAPPY STEEL SG

Zinc plated steel connector with screw gate, ideal for working at height, hauling and rescue manoeuvres.

FEATURES

Colour:	Silver
Swivel:	No
Carabiner properties:	Corrosion resistance
Fallindicator:	No
Gate opening:	22 mm
MBS MAJOR AXIS:	40 kN
MBS GATE OPEN:	15 kN
MBS MINOR AXIS:	15 kN
Form fit:	Key Lock
Carabiner type:	Type H (EN 12275: 2013), Type M (EN 362:2004)
Maximum lifetime:	30 years
Minimum temperature:	-35 °C
Maximum temperature:	45 °C
Standard ANSI:	No
Standard CSA:	No
UIAA compliance:	Yes
Anti-twist device:	No
Locking mechanism:	Screwgate

MATERIAL

Material:	Steel
-----------	-------

DATASHEET

SNAPPY STEEL SG

