DATASHEET

TUNER PRO





GENERAL

Art.Nr:	L-1017-1,3	Standards:	EN 358:2018,EN 795: 2012/B
GTIN:	8053841303030	Net weight:	0.18 kg
E-class number:	40-21-08-13	Gross weight:	0.27 kg
Customs tariff number:	56090000		

DATASHEET

TUNER PRO

The adjustable lanyard is specially designed for working on ropes, at height and for rescue operations and can be used as a lanyard for work positioning and restraint in accordance with EN 358 or for creating anchorage devices in accordance with EN 795-B and CEN TS 16415 for two operators. Despite its compact dimensions and low weight, it offers one of the highest working loads on the market.

At the heart of the system is an innovative regulator with a movable, patented system that guarantees immediate and safe locking of the rope - regardless of the shape of the EN 362-compliant connecting element used. The special geometry of the regulator allows precise and smooth adjustment of the rope length. The tether can be released intuitively with just one hand: simply hold the regulator and press the release button, even under light load.

The retaining rope is equipped with a 9.6 mm thick, lightweight and flexible rope in accordance with EN 1891-A, which is designed for intensive use. The regulator can be attached either directly to the anchorage device or to the harness, depending on requirements. Mounting on the harness brings the controller closer to the user, making it easy to make adjustments even when the anchorage device is out of reach. In addition, the system has an elastic end eyelet to secure the free side of the rope during use and can be combined with rope guards. The lanyard is available in various lengths from 1.3 meters.

FEATURES

Colour:	Orange, Black
Maximum lifetime:	12 years
Minimum temperature:	-30 °C
Maximum temperature:	50 °C
Patent status:	Patent pending
Individually tested:	No
100% quality control:	Yes

DIMENSIONS

length_lanyard:	1.30 m
Lanyard rope diameter:	9.60 mm

MATERIAL

Material:	Aluminium, Polyamide

DATASHEET

TUNER PRO

MORE INFORMATION
TUNER PRO – Versatile lanyard for workplace positioning, restraint systems and rescue at height <https://www.skylotec.com/eu_en/tunerpro>