DATASHEET

# MILAN 2.0 POWER



## GENERAL

| | |
|---|---|
| Art.Nr: | A-029 |
| GTIN: | 4030281155867 |
| E-class number: | 40-21-01-01 |
| Customs tariff number: | 84251900 |

| | |
|---|---|
| Standards: | ANSI Z359.9-2021,EN 1496:2017/A,EN 341: 2011/1A,MEETS CSA Z259.2.3:16/1/B |
| Net weight: | 5.19 kg |
| Gross weight: | 5.19 kg |

DATASHEET

# MILAN 2.0 POWER

MILAN 2.0 POWER is THE special version of the MILAN 2.0 HUB. With the RESCUE DEVICE DRIVER (RDD) <https://www.skylotec.com/eu_en/rdd-fur-milan-2-0-power-a-029-g.html> it offers an option for fast and safe rescue over long distances upwards. In addition, all manual options for rescue and evacuation are available.

With special SEAL PACs <https://www.skylotec.com/eu_en/seal-pac-set-seal-pac.html> an extended lifetime of up to 15 years can be guaranteed, which can even be doubled once within a resealing process to 30 years. Note: When working at heights, a suitable rescue concept based on a risk assessment is essential. MILAN offers a variety of applications for different rescue scenarios. To master these techniques, the user must be carefully trained by a SKYLOTEC-certified instructor who has been specially trained on the device.

## FEATURES

| | |
|---|---|
| Colour: | Black, Orange, White |
| Lifting function: | Yes |
| Max. abseiling height: | 501 m |
| Maximum load 1 person: | 141.00 kg |
| Maximum load 2 persons: | 280.00 kg |
| Maximum lifetime: | 20 years |
| Maximum number of persons: | 2 |
| Maximum load: | 280.00 kg |
| Minimum compatible rope diameter: | 9.00 mm |
| Maximum compatible rope diameter: | 9.00 mm |
| Max. Abseil speed: | 0.90 m/s |
| Minimum temperature: | -35 °C |
| Maximum temperature: | 60 °C |
| Panic function: | No |
| Rescue function: | Yes |

## MATERIAL

| | |
|---|---|
| Material: | Aluminium, Steel, Polyamide |