DATASHEET

PEANUT I



GENERAL

Art.Nr:	HSG-021-2,5-1
GTIN:	4030281181910
E-class number:	40-02-01-03
Customs tariff number:	84798997

Standards:	EN 360:2002,GS-PS-12:2019,RFU PPE-R/11.060,RFU PPE-R/11.085,RFU PPE-R/11.124
Net weight:	1.66 kg
Gross weight:	1.91 kg

DATASHEET

PEANUT I

The compact connecting device PEANUT I with FS90 ALU karabiner convinces with its self-retracting arm, which does not restrict the working radius and ensures that the fall height is extremely low. The all-rounder carabiner with an opening width of 60 mm is suitable for almost all structures and can be opened easily. The fastener is edge-suitable and thus also serves for horizontal securing. PEANUT I contains the One-4-All damper and is therefore suitable for a very wide range of user weights from 50 to 135 kilograms. The 2.5 m long arm makes PEANUT I ideal for securing in scaffolding. The fastener is available in a variety of karabiner variants (aluminium, steel, etc.). A red indicator shows when the strap has been released and provides additional safety.

FEATURES

Colour:	Black, Grey, Orange
Edge approved:	Yes
Maximum lifetime:	10 years
Maximum number of persons:	1
Minimum user weight:	50.00 kg
Maximum user weight vertical:	135.00 kg
Minimum temperature:	-35 °C
Maximum temperature:	45 °C

DIMENSIONS

Rope length:	2.50 m

MATERIAL

Material:	Polyester, Polyamide, Steel, Aluminium