

DATASHEET

BFD Y FLEX



GENERAL

Art.Nr:	L-AUS-0582-1,5
GTIN:	4030281162384
E-class number:	40-02-01-04
Customs tariff number:	56090000

Standards:	AS/NZS 1891.1:2007
Net weight:	2.25 kg
Gross weight:	2.25 kg

DATASHEET

BFD Y FLEX

The elasticised webbing TWIN leg BFD Personal Energy Absorbing range reduce the overall length of the lanyard by 73cm (2mt version), 40cm (1,5mt version) or 25cm (1.2mt version) and are all designed to effectively arrest a fall whilst minimising the shock loads on the body. The 'Tear Tape' technology shock pack utilises a controlled tearing action that is initiated when the lanyard is 'loaded' during the fall and limits the fall arrest forces to below 6kN. The shock pack features a unique Velcro attach cover that provide 100% inspection as well as the potential to clean & dry the pack contents if necessary. The cover is also designed to protect the label pack, conveniently sewn into the tear tape material.

FEATURES

Colour:	Black, White
Fallindicator:	No
Impact force:	6.00 kN
Hand wash:	40 °C
Edge approved:	No
Maximum lifetime:	10 years
Minimum tensile strength:	22.00 kN
Minimum temperature:	-35 °C
Maximum temperature:	45 °C
Rescue loop:	No
Lanyard type:	Y-Version

DIMENSIONS

length_lanyard:	1.50 m
Lanyard rope diameter:	30.00 mm

MATERIAL

Material:	Polyamide, Polyester, Steel
-----------	-----------------------------