DATASHEET

SKYSAFE PRO FLEX



GENERAL

Art.Nr:	L-0777-1,8
GTIN:	4030281296379
E-class number:	40-21-08-10
Customs tariff number:	56090000

Standards:	EN 354:2010,EN 355: 2002,EN 795:2012, RFU PPE-R/11.063, RFU PPE-R/11.074
Net weight:	0.92 kg
Gross weight:	0.92 kg

DATASHEET

SKYSAFE PRO FLEX

ONE4ALL - The SKYSAFE PRO Revolutionary, new, patented energy absorber with the large weight range from 50 - 140kg (110 - 309 lbs.) that always withstands a maximum impact of less than 6 kN at a maximum absorber length of 1.75m (5.7 Feet). The final impact resistance of 22 kN, also in the absorber, before AND after a fall is exceptional as well. SKYSAFE PRO furthermore meets the most relevant international standards in one SINGLE product. UNIQUE: The built-in, adjustable RESCUE LOOPS! As a result, rescuers need not set up a rescue system and hereby save precious time in a rescue! Available in four versions with different carabiner combinations: I-web, Y-web, I-web tie-back, Y-web tie-back.

FEATURES

Colour:	Orange, Black, Grey
Fallindicator:	Yes
Impact force:	6.00 kN
Hand wash:	40 °C
Edge approved:	Yes
Maximum lifetime:	10 years
Minimum tensile strength:	22.00 kN
Minimum temperature:	-35 °C
Maximum temperature:	45 °C
Rescue loop:	Yes
Lanyard type:	I-Version

DIMENSIONS

length_lanyard:	1.80 m
Lanyard rope diameter:	30.00 mm

MATERIAL

Material:	Polyester, Aluminium