

# DATASHEET

## MILAN 2.0



### GENERAL

|                        |               |
|------------------------|---------------|
| Art.Nr:                | A-027         |
| GTIN:                  | 4030281155843 |
| E-class number:        | 40-21-01-01   |
| Customs tariff number: | 84798997      |

|               |   |
|---------------|---|
| Standards:    | ANSI Z359.9-2021, EN 341:2011/1A, MEETS CSA Z259.2.3:16/1/B |
| Net weight:   | 2.29 kg   |
| Gross weight: | 2.29 kg   |

# DATASHEET

## MILAN 2.0

MILAN is THE industrial standard evacuation device worldwide. The centrifugally controlled brake maintains a constant descent speed of 0.9 m/s, thus ensuring fast and safe evacuation. The ultra-robust housing made in Germany is CNC-milled from a solid block aluminium. - suitable for 2-person use and for alternating abseiling - abseiling heights up to 500 m - rescue operations of any kind at any place With special [SEAL PACs](<https://bit.ly/3408bTx>) an extended lifetime of up to 15 years can be guaranteed, which can even be doubled once within a resealing process to 30 years. Note: When working at heights, a suitable rescue concept based on a risk assessment is essential. MILAN offers a variety of applications for different rescue scenarios. To master these techniques, the user must be carefully trained by a SKYLOTEC-certified instructor who has been specially trained on the device.

### FEATURES

|                                   |                      |
|-----------------------------------|----------------------|
| Colour:                           | Black, Orange, White |
| Lifting function:                 | No                   |
| Max. abseiling height:            | 500 m                |
| Maximum load 1 person:            | 141.00 kg            |
| Maximum load 2 persons:           | 280.00 kg            |
| Maximum lifetime:                 | 20 years             |
| Maximum number of persons:        | 2                    |
| Maximum load:                     | 280.00 kg            |
| Minimum compatible rope diameter: | 9.00 mm              |
| Maximum compatible rope diameter: | 9.00 mm              |
| Max. Abseil speed:                | 0.90 m/s             |
| Minimum temperature:              | -35 °C               |
| Maximum temperature:              | 60 °C                |
| Panic function:                   | No                   |
| Rescue function:                  | Yes                  |

### MATERIAL

|           |                             |
|-----------|-----------------------------|
| Material: | Aluminium, Steel, Polyamide |
|-----------|-----------------------------|