

DATASHEET

X-TREM DYNAMIK 11.0



GENERAL

Art.Nr:	R-052-100	Standards:	EN 892:2012+A1: 2016
GTIN:	4030281165385	Net weight:	8.29 kg
E-class number:	40-02-90-06	Gross weight:	9.27 kg
Customs tariff number:	56090000		

DATASHEET

X-TREM DYNAMIK 11.0

X-trem is the low-kink dynamic rope for extreme applications. It is extremely abrasion-resistant, and has very low sheath slip. That means it can be used for many abseiling operations and has a high durability.

FEATURES

Colour:	Orange, Black
---------	---------------

Number of standard falls:	16
---------------------------	----

Dynamic elongation:	32.00
---------------------	-------

Hand wash:	40 °C
------------	-------

Edge approved:	Yes
----------------	-----

Core ratio:	59.50
-------------	-------

Knotability:	0.90
--------------	------

Maximum lifetime:	10 years
-------------------	----------

Maximum catch force:	9.00 kN
----------------------	---------

Minimum temperature:	-35 °C
----------------------	--------

Maximum temperature:	45 °C
----------------------	-------

Melting temperature:	230 °C
----------------------	--------

Rope features:	UV resistance
----------------	---------------

Rope character:	Dynamic rope
-----------------	--------------

Rope construction:	Kernmantel rope
--------------------	-----------------

Static elongation:	7.50
--------------------	------

Weight per meter:	82.00 g
-------------------	---------

DIMENSIONS

Rope length:	100.00 m
--------------	----------

Rope diameter:	11.00 mm
----------------	----------

MATERIAL

Material:	Polyamide
-----------	-----------