DATASHEET

FINCH+





GENERAL

Art.Nr:	L-0811-2
GTIN:	8057733306277
E-class number:	40-21-08-13
Customs tariff number:	56090000

Standards:	EN 12841:2006/C,EN 358:2018,EN 795: 2012/B/C
Net weight:	0.56 kg
Gross weight:	0.56 kg

DATASHEET

FINCH+

The FINCH+ is a multipurpose lanyard for work at height. It is equipped with an adjuster device that bears a control lever and allows for the smooth movement of the rope, without sudden jerks, immediately locking in the position as soon as it is released. It allows for easy recovery and release of the rope, even under tension. The lanyard is used as a work-positioning lanyard in accordance with EN 358 and can be attached to both the lateral and ventral attachment points of a full body harness. It is also used as a temporary anchorage device in accordance with EN 795-B. The lengths from 5 m comply with the technical specification TS 16415-C, which allows the multiple span lifeline to be used by several users at the same time. It can be used in accordance with EN 795-C to create a temporary horizontal singlespan or multiple span lifeline. The device is compliant with all requirements of the standard EN 12841-C for use as descender, except clauses 4.1.2 and 4.1.3 which have not been considered.

FEATURES

Colour:	Black
Fallindicator:	No
Hand wash:	40 °C
Maximum lifetime:	10 years
Minimum tensile strength:	15.00 kN

DIMENSIONS

length_lanyard:	2.00 m
Lanyard rope diameter:	11.00 mm

MATERIAL

Material:	Polyamide, Steel, Aluminium