DATASHEET

X-TREM DYNAMIK 11.0



GENERAL

Art.Nr:	R-052-30	Standards:	EN 892:2012+A1: 2016
GTIN:	4030281165774	Net weight:	2.54 kg
E-class number:	40-02-90-06	Gross weight:	2.54 kg
Customs tariff number:	56090000		

DATASHEET

X-TREM DYNAMIK 11.0

X-trem is the low-kink dynamic rope for extreme applications. It is extremely abrasion-resistant, and has very low sheath slip. That means it can be used for many abseiling operations and has a high durability.

FEATURES

Colour:	Orange, Black
Number of standard falls:	16
Dynamic elongation:	32.00
Hand wash:	40 °C
Edge approved:	Yes
Core ratio:	59.50
Knotability:	0.90
Maximum lifetime:	10 years
Maximum catch force:	9.00 kN
Minimum temperature:	-35 °C
Maximum temperature:	45 °C
Melting temperature:	230 °C
Rope features:	UV resistance
Rope character:	Dynamic rope
Rope construction:	Kernmantel rope
Static elongation:	7.50
Weight per meter:	82.00 g

DIMENSIONS

Rope length:	30.00 m
Rope diameter:	11.00 mm

MATERIAL

Material:	Polyamide