DATASHEET

# Q-LINK D 08



## GENERAL

| | | | |
|---|---|---|---|
| Art.Nr: | H-323-08 | Standards: | EN 12275:2013/Q,EN 362:2004/Q,UIAA 121 |
| GTIN: | 3351770019370 | Net weight: | 0.09 kg |
| E-class number: | 40-21-07-12 | Gross weight: | 0.09 kg |
| Customs tariff number: | 73269098 | | |

DATASHEET

# Q-LINK D 08

Galvanized-steel quick link, triangular shaped Ø 8 mm, extremely sturdy and designed to withstand high loads on all axes. Ideal as a closing loop of the two attachment points of the harness for work at height.

When closed with a wrench, it becomes a semi-permanent anchor.

## FEATURES

| | |
|---|---|
| Colour: | Silver |
| Swivel: | No |
| Carabiner properties: | Corrosion resistance |
| Fallindicator: | No |
| Gate opening: | 10 mm |
| MBS MAJOR AXIS: | 27 kN |
| MBS MINOR AXIS: | 10 kN |
| Form fit: | Threaded end |
| Carabiner type: | Type Q (EN 12275: 2013), Type Q (EN 362:2004) |
| Maximum lifetime: | 30 years |
| Minimum temperature: | -35 °C |
| Maximum temperature: | 45 °C |
| Standard ANSI: | No |
| Standard CSA: | No |
| UIAA compliance: | Yes |
| Anti-twist device: | No |
| Locking mechanism: | Screwgate |

## MATERIAL

| | |
|---|---|
| Material: | Steel |