DATASHEET

Q-LINK D 10



GENERAL

Art.Nr:	H-323-10	Standards:	EN 12275:2013/Q,EN 362:2004/Q,UIAA 121
GTIN:	3351770010773	Net weight:	0.15 kg
E-class number:	40-21-07-12	Gross weight:	0.15 kg
Customs tariff number:	73269098		

DATASHEET

Q-LINK D 10

Galvanized-steel quick link, triangular shaped Ø 10 mm, extremely sturdy and designed to withstand high loads on all axes. Ideal as a closing loop of the two attachment points of the harness for work at height.

When closed with a wrench, it becomes a semi-permanent anchor.

FEATURES

Colour:	Silver
Swivel:	No
Carabiner properties:	Corrosion resistance
Fallindicator:	No
Gate opening:	12 mm
MBS MAJOR AXIS:	45 kN
MBS MINOR AXIS:	10 kN
Form fit:	Threaded end
Carabiner type:	Type Q (EN 12275: 2013), Type Q (EN 362:2004)
Maximum lifetime:	30 years
Minimum temperature:	-35 °C
Maximum temperature:	45 °C
Standard ANSI:	No
Standard CSA:	No
UIAA compliance:	Yes
Anti-twist device:	No
Locking mechanism:	Screwgate

MATERIAL

Material:	Steel