

DATASHEET

MOBILFIX TERMINAL DE TYP 52



GENERAL

Art.Nr:	AP-TYP-52	Standards:	ABZ,EAD 331072-00-0601
GTIN:	4030281277583	Net weight:	0.14 kg
E-class number:	40-02-01-90	Gross weight:	0.22 kg
Customs tariff number:	73269098		

DATASHEET

MOBILFIX TERMINAL DE TYP 52

The removable single anchor point MOBILFIX (AP-018) made of stainless steel is designed for regularly recurring work, such as window cleaning. It is tested and certified according to EN 795: 2012, CEN/TS 16415: 2013. The installation sleeve (AP-type-52), for holding the MOBILFIX, is permanently installed in concrete at the point of use. The sleeve has a European Technical Assessment (ETA -16/0790) and is tested and certified according to EN 795: 2012, CEN/TS 16415: 2013. It lies flush in the wall or ceiling and is closed by the internal spring plug. This prevents the penetration of dirt and is visually inconspicuous. The installation is carried out by means of adhesive mortar. The minimum thickness of the substrate is 107 mm. The patented shape of the MOBILFIX prevents the carabiner from dragging on the wall.

- Single anchor point, especially as an anchor point for window cleaners.
- Fastening with adhesive mortar in concrete, AK 1, approval for 3 persons

FEATURES

Colour:	Silver
Anchor point type:	Stationary anchor point
Type mounting base:	Concrete
Thickness mounting base:	170 mm
Maximum number of persons:	3
Rope access technique:	No

DIMENSIONS

Construction height:	0 mm
Foot plate length:	0 mm
Foot plate width:	0 mm
Hole spacing a:	0 mm
Hole spacing b:	0 mm
Minimum area required:	9.00 cm ²
Diameter pillar:	20 mm
Diameter bore:	24 mm

MATERIAL

Material:	Stainless Steel
-----------	-----------------