DATASHEET

SKYSAFE PRO+



GENERAL

Art.Nr:	L-0837-1C8
GTIN:	4030281029311
E-class number:	40-21-08-10
Customs tariff number:	56090000

Standards:	EN 355:2002,EN 795: 2012/B,RFU PPE-R/11.063,RFU PPE-R/11.074
Net weight:	2.06 kg
Gross weight:	2.35 kg

DATASHEET

SKYSAFE PRO+

Experience maximum safety and efficiency when working at height with the SKYSAFE PRO+. This innovative lanyard with compact energy absorber enables smooth and efficient movement even in confined structures, guaranteeing trouble-free operation. The unique energy absorbers limit the fall arrest forces to less than 6 kN in the event of a fall, with a user weight range of 50 to 150 kg. Thanks to the advanced 'short-circuit safety', the lanyard guarantees maximum safety even in the event of misuse. SKYSAFE PRO+ is safe to use even with sharp edges >0.5 mm radius and, thanks to the integrated drop indicator, you can quickly and easily check its readiness for use at any time.
SKYSAFE PRO+ expands your selection options with a variety of carabiner options to choose the optimum configuration for your needs. With a length of 1.80 m, the SKYSAFE PRO+ ensures maximum freedom of movement and increases comfort at work. Certified in accordance with EN 354, EN 355, EN 795/B, RFU 11.074, the SKYSAFE PRO+ guarantees the highest standards of safety and quality.

FEATURES

Colour:	Black, Orange
Fallindicator:	Yes
Impact force:	6.00 kN
Hand wash:	40 °C
Edge approved:	Yes
Maximum lifetime:	10 years
Minimum tensile strength:	22.00 kN
Min. temperature:	-35 °C
Max. temperature:	45 °C
Rescue loop:	Yes
Lanyard type:	Y-Version
Connector:	FS64 ALU

DIMENSIONS

Rope length:	1.80 m
length_lanyard:	1.80 m
Lanyard rope diameter:	30.00 mm

MATERIAL

Material:	Polyester, Polyamide, Aluminium