DATASHEET

SKYSAFE PRO+



GENERAL

Art.Nr:	L-0849-1C8
GTIN:	4030281312123
E-class number:	40-21-08-10
Customs tariff number:	56090000

Standards:	EN 355:2002,EN 795: 2012/B,RFU PPE-R/11.063,RFU PPE-R/11.074
Net weight:	2.50 kg
Gross weight:	2.88 kg

DATASHEET

SKYSAFE PRO+

The SKYSAFE PRO+ is an innovative lanyard for working at height and combines the highest safety standards with maximum efficiency. Equipped with an ultra-compact energy absorber, it enables smooth movement even in narrow structures, ensuring trouble-free work. The specially developed shock absorbers reliably limit the fall arrest forces to less than 6 kN in the event of a fall - and that with a wide user weight range of 50 to 150 kg.

The integrated short-circuit protection, which also offers protection in the event of misuse and therefore significantly reduces the risks of incorrect use, is particularly noteworthy. The lanyard is also approved for use on sharp edges with a radius of more than 0.5 mm. An integrated drop indicator enables quick and easy verification of readiness for use at any time.

With a length of 1.80 meters, the SKYSAFE PRO+ offers optimum freedom of movement and high wearing comfort. The system can be customized thanks to a wide range of carabiner options. The EN 354, EN 355, EN 795/B and RFU 11.074 certifications underline the quality and safety of this high-performance lanyard.

FEATURES

Colour:	Black, Orange
Fallindicator:	Yes
Impact force:	6.00 kN
Hand wash:	40 °C
Edge approved:	Yes
Maximum lifetime:	10 years
Minimum tensile strength:	22.00 kN
Min. temperature:	-35 °C
Max. temperature:	45 °C
Rescue loop:	Yes
Lanyard type:	Y-Version
Connector:	FS110

DIMENSIONS

Rope length:	1.80 m
length_lanyard:	1.80 m
Lanyard rope diameter:	30.00 mm

MATERIAL

Material:	Polyester, Polyamide, Aluminium