DATASHEET

QUICK'UP+ L





GENERAL

Art.Nr:	H-574-805-LEFT	Standards:	EN 12841:2024/B,EN 567:2013
GTIN:	8053841302958	Net weight:	0.22 kg
Customs tariff number:	76169990	Gross weight:	0.29 kg

DATASHEET

QUICK'UP+ L

Left-hand light alloy ascender handle with ergonomic rubber grip. Ideal for rope ascent, hoist construction and lifting material.

Main features:

• overmolded, ergonomic handle ascender, designed for greater efficiency when pulling and increased resistence to wear and tear;
• cam opening lever usable with one hand; patented system for unlocking the cam, with just one downwards movement necessary;
steel cam, manufactured with technology that implements the resistance to wear and tear. Equipped with a set of teeth that protects the wear of the rope, but it is equally effective in blocking and ascending the rope. It also has three slots to prevent the accumulation of mud and reduce the effort needed to slide the device up the rope under any condition (muddy rope, frozen etc.);
• two attachment holes for various possible uses, anti-inversion cam system, secondary hole for connecting a quick link for an etrier.

FEATURES

Colour:	Black, Grey
Maximum lifetime:	12 years
Min. temperature:	-29 °C
Max. temperature:	40 °C
UIAA compliance:	Yes
Working Load Limit:	140 kg
Patent status:	Patented
Individually tested:	Yes
Ascender type:	hand_ascenders

DIMENSIONS

Min. rope diameter / EN 12841:	10 mm
Max. rope diameter / EN 12841:	13 mm
Min. rope diameter / EN 567:	8 mm
Max. rope diameter / EN 567:	13 mm
Product length:	189.00 mm
Product width:	93.00 mm

MATERIAL

Material:	Aluminium