DATASHEET

ALUFIX



GENERAL

Art.Nr:	AP-003
GTIN:	4030281042556
E-class number:	40-02-01-90
Customs tariff number:	76169990

Standards:	ANSI/ASSP Z359.18-2017,CEN/TS 16415, EN 795:2012/A
Net weight:	0.37 kg
Gross weight:	0.37 kg

DATASHEET

ALUFIX

Tested in accordance with EN 795/A. As structurally anchored anchor points / devices are no longer subject to the PPE Directive, they may no longer be CE marked. In Germany, building authority approval is required for these products. In Europe, different national regulations apply to these products and approval may be required in individual cases. The Alufix is suitable for mounting on masonry made of concrete or stone as well as on steel structures. Wide plate with an eyelet for securing a person and 2 holes with a diameter of 14 mm for fastening this plate, the assembly is made of aluminum and is guaranteed rustproof.

FEATURES

Colour:	Grey
Anchor point type:	Stationary anchor point
Mounting type:	Concrete screw, Fix anchor, Machine screws, Wood construction screws
Maximum lifetime:	20 years
Max. number of persons:	3
Maximum load:	4400.00 kg
Min. temperature:	-20 °C
Max. temperature:	80 °C
Rope access technique:	Yes

DIMENSIONS

Construction height:	70 mm
Foot plate length:	131 mm
Foot plate width:	69 mm
Hole spacing a:	0 mm
Hole spacing b:	100 mm
Diameter pillar:	0 mm
Diameter bore:	13 mm
Product heigth:	70.00 mm

MATERIAL

Material:	Aluminium