DATASHEET

# CLIMBING PROTECTION LADDER



## GENERAL

| | | | |
|---|---|---|---|
| Art.Nr: | TAC-0010-1400 | Net weight: | 7.37 kg |
| GTIN: | 4030281105398 | Gross weight: | 7.37 kg |
| E-class number: | 40-02-01-90 | | |
| Customs tariff number: | 73269030 | | |

DATASHEET

# CLIMBING PROTECTION LADDER

The CLIMBING PROTECTION LADDER climbing protection ladder for the SKYTAC climbing protection system is made of steel and consists of robust rungs with a non-slip surface. The rung spacing is 280 mm. The profile of the guide rail with coupling piece is 50 x 30 mm without fastening. A mounting distance of 1,400 mm - 1,680 mm is recommended. The step width per side is 150 mm. The maximum overhang is 8°, more is possible with the SPEED fall arrester. All system units are supplied including the required couplings. It is available in lengths from 560 mm to 5600 mm.

## FEATURES

| | |
|---|---|
| Colour: | Silver |
| Max. number of persons: | 1 |
| Maximum load: | 150.00 kg |
| Rope access technique: | No |
| Vertical systems: | Vertical rail system |

## DIMENSIONS

| | |
|---|---|
| Rail length: | 1.40 m |
| Rail width: | 0.05 m |
| Max height: | 5600 mm |
| Min. height: | 560 mm |

## MATERIAL

| | |
|---|---|
| Material: | Steel |