DATASHEET

Q-LINK TWIST



GENERAL

Art.Nr:	H-322-10	Standards:	EN 12275:2013/Q,EN 362:2004/Q,UIAA 121
GTIN:	3351770020185	Net weight:	0.11 kg
E-class number:	40-21-07-12	Gross weight:	0.11 kg
Customs tariff number:	73269098		

DATASHEET

Q-LINK TWIST

Galvanized-steel quick link with oval shaped Ø 8 mm, twisted 90°.

Main features:

• extremely sturdy;
• designed to withstand high loads on all axes;
• ideal for lowering, as an anchor connector on permanently installed
quickdraws, work at height, industrial safety and rescue;
• when closed with a wrench, it becomes a semi-permanent anchor.

FEATURES

Colour:	Silver
Gate opening:	17 mm
MBS MAJOR AXIS:	32 kN
MBS MINOR AXIS:	10 kN
Form fit:	Threaded end
Carabiner type:	Type Q (EN 12275: 2013), Type Q (EN 362:2004)
Maximum lifetime:	30 years
Min. temperature:	-30 °C
Max. temperature:	50 °C
UIAA compliance:	Yes
Anti-twist device:	No
100% quality control:	Yes
Hard coated:	No
Locking mechanism:	Screwgate

DIMENSIONS

Size:	One Size
Product length:	104.00 mm
Product width:	29.00 mm

MATERIAL

Material:	Steel