DATASHEET

Q-LINK 10



GENERAL

Art.Nr:	H-320-10	Standards:	EN 12275:2013/Q,EN 362:2004/Q,UIAA 121
GTIN:	3351770010742	Net weight:	0.14 kg
E-class number:	40-21-07-12	Gross weight:	0.14 kg
Customs tariff number:	73269098		

DATASHEET

Q-LINK 10

Galvanized-steel quick link, oval shaped Ø 10 mm.

Main features:

- extremely sturdy;
- esigned to withstand high loads on all axes;
- ideal to be used as a lowering anchorage, for fixed quickdraws, work at height, industrial safety and rescue;
- when closed with a wrench, it becomes a semi-permanent anchor.

FEATURES

Colour:	Silver
Swivel:	No
Carabiner properties:	Corrosion resistance
Gate opening:	12 mm
MBS GATE:	55 kN
MBS MAJOR AXIS:	55 kN
MBS GATE OPEN:	10 kN
MBS MINOR AXIS:	10 kN
Form fit:	Threaded end
Carabiner type:	Type Q (EN 12275: 2013), Type Q (EN 362:2004)
Maximum lifetime:	30 years
Min. temperature:	-30 °C
Max. temperature:	50 °C
Standard ANSI:	Yes
Standard CSA:	Yes
UIAA compliance:	Yes
Anti-twist device:	No
100% quality control:	Yes
Hot forged:	No
Hard coated:	No
Locking mechanism:	Screwgate

DIMENSIONS

Size:	Not relevant
Product length:	89.00 mm

DATASHEET

Q-LINK 10

Product width:	44.00 mm
Product heigth:	0.00 mm

MATERIAL

Material:	Steel