DATASHEET

LOOP 35 KN



GENERAL

Art.Nr:	L-0010-GE-1,2
GTIN:	4030281047407
E-class number:	40-21-08-11
Customs tariff number:	63079098

Standards:	ANSI/ASSP Z359.18-2017,CEN/TS 16415:2013,CSA Z259.15-2022,EN 354:2010,EN 566:2017,EN 795-B:2012
Net weight:	0.16 kg
Gross weight:	0.16 kg

DATASHEET

LOOP 35 KN

The black and yellow polyamide webbing slings can be used as a mobile anchor point. To make the different lengths easier to distinguish, the stitching colours vary. The slings are available in lengths of 0.6 m, 0.8 m, 1 m, 1.2 m, 1.5 m, 1.8 m and 2 m. They have a width of 25 mm, a load capacity of 35 kN and are approved for simultaneous use by up to three persons in accordance with the technical specification CEN/TS 16415:2013. They are mainly used in the construction industry.

The stitching colour varies depending on the length of the LOOP:

- L-0010-GE-0.6: grey
- L-0010-GE-0.8: orange
- L-0010-GE-1: blue
- L-0010-GE-1.2: green
- L-0010-GE-1.5: grey
- L-0010-GE-1.8: grey
- L-0010-GE-2: pink

FEATURES

Colour:	Yellow
Fallindicator:	No
Hand wash:	40 °C
Edge approved:	No
Maximum lifetime:	10 years
Minimum tensile strength:	35.00 kN
Min. temperature:	-35 °C
Max. temperature:	45 °C

DIMENSIONS

length_lanyard:	1.20 m

MATERIAL

Material:	Polyamide