

DATASHEET

MOBILFIX



GENERAL

Art.Nr:	AP-018
---------	--------

GTIN:	4030281174028
-------	---------------

E-class number:	40-02-01-90
-----------------	-------------

Customs tariff number:	73269098
------------------------	----------

Standards:	CEN/TS 16415:2013, EN 795:2012/B
------------	-------------------------------------

Net weight:	0.25 kg
-------------	---------

Gross weight:	0.31 kg
---------------	---------

DATASHEET

MOBILFIX

The MOBILFIX (AP-018) removable single-point anchor, made of stainless steel, is designed for regularly recurring tasks, such as window cleaning. It is tested and certified in accordance with EN 795:2012 and CEN/TS 16415:2013. The mounting sleeve (AP Type 52), which holds the MOBILFIX, is permanently installed in concrete at the work site. The sleeve has a European Technical Assessment (ETA-16/0790) and is tested and certified in accordance with EN 795:2012 and CEN/TS 16415:2013. It sits flush with the wall or ceiling and is sealed by an internal spring-loaded plug. This prevents the ingress of dirt and ensures a discreet appearance. Installation is performed using adhesive mortar. The minimum thickness of the substrate is 107 mm. The patented design of the MOBILFIX prevents the carabiner from scraping against the wall.

- Single anchor point, specifically designed for window cleaners
- Installation with adhesive mortar in concrete, AK 1, approved for 3 people

FEATURES

Colour:	Black
Anchor point type:	Mobile anchor point
Type mounting base:	Concrete
Max. number of persons:	3
Min. temperature:	-20 °C
Max. temperature:	80 °C
Rope access technique:	No

DIMENSIONS

Construction height:	50 mm
Foot plate length:	0 mm
Foot plate width:	0 mm
Hole spacing a:	0 mm
Hole spacing b:	0 mm
Diameter pillar:	0 mm
Diameter bore:	24 mm

MATERIAL

Material:	Stainless Steel
-----------	-----------------