SKYLOTEC

DATASHEET

FS 90 ALU



GENERAL

Art.Nr:	H-015	Standards:	EN 362:2004/A
GTIN:	4030281276081	Net weight:	0.47 kg
E-class number:	40-21-07-12	Gross weight:	0.49 kg
Customs tariff number:	76169990		

DATASHEET

FS 90 ALU

The SKYLOTEC FS 90 ALU is a large aluminum carabiner designed specifically for demanding applications in work at height, emergency rescue services, and special operations. Thanks to its robust construction and large opening width of up to 60 mm, it is ideal for clipping into larger anchor points such as scaffolding tubes, rope systems, or rescue systems. Thanks to its ergonomic one-handed or palm-operated safety lock, the carabiner allows for quick and safe operation even under difficult conditions. The high-strength aluminum alloy construction ensures an optimal balance of stability and weight, making it reliable for daily professional use. With a breaking load of 22 kN along the main axis, the FS 90 ALU meets the requirements of the EN 362-A standard and thus offers a high level of safety. The Key-Lock nose also prevents snagging when clipping in and out and ensures smooth handling. The FS 90 ALU is the ideal choice for users who need a high-performance, durable, and easy-to-use connection solution for complex application scenarios.

FEATURES

Colour:	Orange, Silver
Swivel:	No
Carabiner properties:	Corrosion resistance
Fallindicator:	No
Gate opening:	61 mm
MBS MAJOR AXIS:	22 kN
Form fit:	Key Lock
Carabiner type:	Type A (EN 362:2004)
Maximum lifetime:	30 years
Min. temperature:	-35 °C
Max. temperature:	45 °C
Standard ANSI:	No
Standard CSA:	No
UIAA compliance:	No
Anti-twist device:	Yes
Locking mechanism:	Palm Squezze

MATERIAL

Material:	Aluminium