

DATASHEET

SURFACE MOUNT FALL ARREST ANCHOR



GENERAL

Art.Nr: AP-SUR-MOUNT-FALL

E-class number: 40-02-01-90

Standards: AS/NZS 5532:2013

Net weight: 1.25 kg

Gross weight: 1.25 kg

DATASHEET

SURFACE MOUNT FALL ARREST ANCHOR

The SURFACE MOUNT FALL ARREST ANCHOR is a stainless steel anchor point designed specifically for trapezoidal steel sheet profiles. It is certified to AS/NZS 5532:2013 and designed for professional use in fall protection.

The anchor point can be used as a single anchor point for personal protective equipment as well as a substructure for rope systems. It thus combines two key functions into one solution and supports flexible planning on suitable trapezoidal sheet metal profiles.

For particularly efficient installation, the SURFACE MOUNT FALL ARREST ANCHOR is delivered pre-assembled and ready for installation. The swivel bracket, along with the included sheet metal screws and bulb-type rivets, enable quick and easy installation. The stainless steel version provides a robust solution for demanding applications.

FEATURES

Colour:	Silver
Anchor point type:	Stationary anchor point
Type mounting base:	Trapezoidal sheet metal
Mounting type:	Sheet metal screws, Rivets
Maximum lifetime:	15 years
Max. number of persons:	1
Min. temperature:	-20 °C
Max. temperature:	80 °C
Rope access technique:	No

DIMENSIONS

Construction height:	80 mm
Foot plate length:	285 mm
Foot plate width:	275 mm
Hole spacing a:	257 mm
Hole spacing b:	228 mm
Diameter pillar:	0 mm
Diameter bore:	8 mm
Product length:	275.00 mm
Product width:	285.00 mm
Product height:	80.00 mm

MATERIAL

Material:	Stainless Steel
-----------	-----------------