

DATASHEET

SURFACE MOUNT ROPE ACCESS ANCHOR



GENERAL

Art.Nr: AP-SUR-MOUNT-ROPE

E-class number: 40-02-01-90

Standards: AS/NZS 5532:2013

Net weight: 2.20 kg

Gross weight: 2.20 kg

DATASHEET

SURFACE MOUNT ROPE ACCESS ANCHOR

The SURFACE MOUNT ROPE ACCESS ANCHOR is a stainless steel anchor point specifically designed for trapezoidal steel sheet profiles. It is certified to AS/NZS 5532:2013 and is suitable for various applications in fall protection and rope access.

The anchor point can be used as a single anchor point for personal protective equipment, as a rope access anchor point, and as a substructure for rope systems. It thus combines multiple applications into a single solution and supports flexible planning on suitable trapezoidal sheet metal profiles.

For particularly easy installation, the SURFACE MOUNT ROPE ACCESS ANCHOR is delivered pre-assembled and ready for installation. Stainless steel sheet metal screws and bulb-type rivets are included, allowing the anchor point to be installed quickly and efficiently. The stainless steel construction ensures a robust solution for professional use.

FEATURES

Colour:	Silver
Anchor point type:	Stationary anchor point
Type mounting base:	Trapezoidal sheet metal
Mounting type:	Sheet metal screws, Rivets
Maximum area required:	0.15 m ²
Maximum lifetime:	15 years
Max. number of persons:	1
Min. temperature:	-20 °C
Max. temperature:	80 °C
Rope access technique:	Yes

DIMENSIONS

Construction height:	80 mm
Foot plate length:	550 mm
Foot plate width:	275 mm
Hole spacing a:	251 mm
Hole spacing b:	520 mm
Diameter pillar:	0 mm
Diameter bore:	8 mm

MATERIAL

Material:	Stainless Steel
-----------	-----------------