

DATASHEET

RAPTOR C20 HUB



GENERAL

Art.Nr:	HSG-044-20	Standards:	EN 1496:2017/A,EN 360:2002
GTIN:	4030281224075	Net weight:	10.68 kg
E-class number:	40-02-01-03	Gross weight:	10.68 kg
Customs tariff number:	84798997		

DATASHEET

RAPTOR C20 HUB

The RAPTOR HUB retractable type fall arrester with a 20 m steel cable and automatic blocking function enables safe working at height and depth. RAPTOR HUB is in contrast to the RAPTOR additionally equipped with a rescue lifting device, which can be activated in an emergency and allows a quick rescue. After verification by a competent person, the device is ready for use again after the use of the rescue lifting device, which increases its economic efficiency.

RAPTOR HUB offers maximum application possibilities, as it can be used both independently on anchor points according to EN795 and in combination with an individual holder on the TRIBOC, JACKPOD TRI and JACKPOD DAVIT mobile anchor points. The respective holder can remain attached to the mobile anchor points when the device is removed.

RAPTOR HUB has a modular design so that subassemblies can be replaced, which increases the longevity of the devices and leads to lower maintenance costs. The retractable type fall arrester has two visible fall indicators, which indicate the product's functionality from the outside. A red indicator signals to the user as soon as the device needs to be checked. The sophisticated housing design also allows for space-saving storage that is easy on the device.

The device is certified according to EN 360:2002, EN 1496:2017/A and secures a person with a maximum user weight of 140 kg.

FEATURES

Colour:	Black
Edge approved:	No
Maximum lifetime:	20 years
Max. number of persons:	1
Min. user weight:	40.00 kg
Max. user weight horizontal:	0.00 kg
Max. user weight vertical:	140.00 kg
Min. temperature:	-35 °C
Max. temperature:	45 °C

DIMENSIONS

Rope length:	20.00 m
--------------	---------

MATERIAL

Material:	Various
-----------	---------