DATASHEET

LORY PRO



GENERAL

Art.Nr:	A-041
GTIN:	4030281280163
E-class number:	40-21-01-01
Customs tariff number:	84798997

Standards:	ANSI/ASSP Z359.3-2019,ANSI/ASSP Z359.9-2021,CSA Z259.11-17,EN 12841:2024/C,EN 341:2011/2A,EN 795:2012/B
Net weight:	0.37 kg
Gross weight:	0.41 kg

DATASHEET

LORY PRO

LORY is a robust descender and belay device. Its various application areas make the Lory your reliable companion for rope access and rescue (abseiling up to 225 kg load). LORY is used for work positioning, as a restraining device at roofs or slab edges, as a temporary anchor or for fall arrest in flexible cable systems. With LORY, the belaying person can easily feed and take rope. When using the device correctly, it blocks automatically in case of a fall. The LORY PRO model with its unimpeded movement of the cam is the ideal device for industrial purposes. It is equipped with a descent handle that ensures secured and controlled abseiling. The double-stop function blocks if the handle is pulled overly in panic and provides extra safety.

FEATURES

Colour:	Black, Grey
Lifting function:	No
Max. abseiling height:	190 m
Maximum lifetime:	30 years
Max. number of persons:	2
Maximum load:	225.00 kg
Max. Abseil speed:	2.00 m/s
Min. temperature:	-20 °C
Max. temperature:	60 °C
Panic function:	Yes
Rescue function:	Yes
Working Load Limit:	225 kg

DIMENSIONS

Min. rope diameter single ropes:	8.90 mm
Max. rope diameter single ropes:	12.00 mm
Min. rope diameter half & twin ropes:	0.00 mm
Max. rope diameter half & twin ropes:	0.00 mm

MATERIAL

Material:	Aluminium, Stainless Steel