DATASHEET

# ACTSAFE EQUIPMENT LIFTING ROPE



## GENERAL

| | | | |
|---|---|---|---|
| Art.Nr: | R-143-200 | Net weight: | 17.16 kg |
| GTIN: | 4030281293033 | Gross weight: | 17.16 kg |
| E-class number: | 40-02-90-06 | | |
| Customs tariff number: | 56090000 | | |

DATASHEET

# ACTSAFE EQUIPMENT LIFTING ROPE

The robust 11 mm static rope was specially developed to withstand heavy loads.
The Equipment Lifting Rope (ELR) in combination with the ActSafe Power Ascender
is approved as an equipment lifting system according to the Machinery
Directive. This rope is not PPE and must not be used for lifting persons.
Available in several different lengths with 2 sewn end terminations.

Further information:

Discover the POWER ASCENDERS product range. Find out more about the various models, their applications and their innovative features on our overview page – complete with interactive animations and videos.

more information <https://www.skylotec.com/eu_en/power-ascenders>

**FEATURES**

| | |
|---|---|
| Colour: | Black |
| Hand wash: | 40 °C |
| Edge approved: | No |
| Maximum lifetime: | 10 years |
| Minimum tensile strength: | 32.00 kN |
| Min. temperature: | -35 °C |
| Max. temperature: | 45 °C |
| Shrinkage: | 4.00 |
| Rope character: | Static rope |
| Rope construction: | Kernmantel rope |
| Static elongation: | 3.00 |
| Weight per meter: | 75.00 g |

**DIMENSIONS**

| | |
|---|---|
| Rope length: | 200.00 m |
| Rope diameter: | 11.00 mm |

**MATERIAL**

| | |
|---|---|
| Material: | Polyamide |