DATASHEET

# CORD 6.0



## GENERAL

| | | | |
|---|---|---|---|
| Art.Nr: | R-109-100-S | Standards: | EN 564:2023 |
| GTIN: | 4030281120759 | Net weight: | 2.40 kg |
| E-class number: | 40-02-90-06 | Gross weight: | 2.40 kg |
| Customs tariff number: | 56090000 | | |

# DATASHEET

# CORD 6.0

The CORD 6.0 is a sturdy paracord with a 6 mm diameter that's comfortable to handle. It's suitable for a wide range of applications where a paracord that's easy to control, has a good grip, and can withstand heavy loads is needed. Its larger diameter makes it easy to guide, knot, and integrate into existing gear.

The rope is available in 100-meter lengths, providing a flexible rope reserve for a variety of applications. This makes the CORD 6.0 particularly suitable for professional applications where a larger rope reserve is needed.

Made of polyamide, the CORD 6.0 provides a reliable material base for daily use. It complies with the EN 564:2023 standard, has a minimum breaking load of 9.90 kN, and a minimum breaking load with a figure-eight knot of 6.70 kN.
Weighing 27.00 g per meter and featuring UV resistance, it is designed for demanding applications.

| **FEATURES** | |
|---|---|
| Colour: | Black |
| Hand wash: | 40 °C |
| Edge approved: | No |
| Core ratio: | 43.30 |
| Maximum lifetime: | 10 years |
| Minimum tensile strength: | 9.90 kN |
| Minimum strength figure eight knot: | 6.70 kN |
| Min. temperature: | -35 °C |
| Max. temperature: | 45 °C |
| Melting temperature: | 210 °C |
| Rope features: | UV resistance |
| Rope character: | Cord |
| Static elongation: | 7.60 |
| Weight per meter: | 27.00 g |

| **DIMENSIONS** | |
|---|---|
| Rope length: | 100.00 m |
| Rope diameter: | 6.00 mm |

| **MATERIAL** | |
|---|---|
| Material: | Polyamide |