DATASHEET

OVX SG



GENERAL

Art.Nr:	H-298-SG
GTIN:	8057733308899
E-class number:	40-21-07-12
Customs tariff number:	76169990

Standards:	EN 12275:2013,EN 12275:2013/B,EN 362:2004,EN 362: 2004/B,UIAA 121
Net weight:	0.06 kg
Gross weight:	0.07 kg

DATASHEET

OVX SG

Hot-forged light-alloy oval carabiner with reduced dimensions and screw-lock gate. Ideal for rope access work, work at height and rescue operations, in particular where space for manoeuvring is limited.
Main features:

- only 95 mm long, to leave more room for manoeuvres;
- curved shape of the spine, for improved handling and to maximize gate opening;
- oval shape, for optimal placement of equipment and ropes;
- increased cross-section at contact points, for enhanced rope glide and wear resistance;
- the profile between the nose and the interior of the connector is shaped with no discontinuities, which makes it easier to clip and unclip to anchors, tools and ropes;
- catch-free closure.

FEATURES

Colour:	Orange, Anthracite
Swivel:	No
Carabiner properties:	Corrosion resistance
Fallindicator:	No
Gate opening:	17 mm
MBS MAJOR AXIS:	24 kN
MBS GATE OPEN:	7 kN
MBS MINOR AXIS:	9 kN
Form fit:	Key Lock
Carabiner type:	Type B (EN 12275: 2013), Type B (EN 362:2004)
Maximum lifetime:	30 years
Min. temperature:	-35 °C
Max. temperature:	45 °C
Standard ANSI:	No
Standard CSA:	No
UIAA compliance:	Yes
Anti-twist device:	No
Locking mechanism:	Screwgate

MATERIAL

Material:	Aluminium

DATASHEET

OVX SG