DATASHEET

MILAN 2.0



GENERAL

Art.Nr:	A-027
GTIN:	4030281155843
E-class number:	40-21-01-01
Customs tariff number:	84798997

Standards:	ANSI Z359.9-2021,EN 341:2011/1A,MEETS CSA Z259.2.3:16/1/B
Net weight:	2.37 kg
Gross weight:	2.37 kg

DATASHEET

MILAN 2.0

MILAN is THE global industrial standard for evacuation devices. The centrifugal brake maintains a constant descent speed of 0.9 m/s, ensuring a fast and safe evacuation. The ultra-robust housing, made in Germany, is CNC-machined from a solid block of aluminum. - Suitable for use by two people and for shuttle operations - Descent heights up to 500 m - Rescue operations of any kind, anywhere With specialSEAL PAC <https://www.skylotec.com/eu_en/SEAL-PAC/P-SET-SEAL-PAC>, an extended service life of up to 15 years can be guaranteed, which can even be doubled to 30 years on a one-time basis. Note: When working at heights, a suitable rescue plan based on a risk assessment is essential. MILAN offers a wide range of applications for various rescue scenarios. To master these techniques, thorough training <https://www.skylotec.com/eu_en/trainings/climbing-rescue-with-milan/> of the user by a SKYLOTEC-certified instructor who has received specialized training on the device.

FEATURES

Colour:	Black, Orange, White
Lifting function:	No
Max. abseiling height:	500 m
Max. load 1 person:	141.00 kg
Max. load 2 persons:	280.00 kg
Maximum lifetime:	20 years
Max. number of persons:	2
Maximum load:	280.00 kg
Minimum compatible rope diameter:	9.00 mm
Maximum compatible rope diameter:	9.00 mm
Max. Abseil speed:	0.90 m/s
Min. temperature:	-35 °C
Max. temperature:	60 °C
Panic function:	No
Rescue function:	Yes

MATERIAL

Material:	Aluminium, Steel, Polyamide