DATASHEET

MILAN 2.0 HUB



GENERAL

Art.Nr:	A-028
GTIN:	4030281155850
E-class number:	40-21-01-01
Customs tariff number:	84798997

Standards:	ANSI Z359.9-2021,EN 1496:2017/A,EN 341: 2011/1A,MEETS CSA Z259.2.3:16/1/B
Net weight:	5.25 kg
Gross weight:	5.25 kg

DATASHEET

MILAN 2.0 HUB

MILAN 2.0 HUB is THE industry-standard rescue device with an additional lifting function. Using the handwheel, the victim can be lifted a short distance to release their lanyard and lower them safely. The device is optimized for assisted personnel rescue. Note: When working at heights, a suitable rescue plan based on a risk assessment is essential. MILAN offers a wide range of applications for various rescue scenarios. To master these techniques, users must undergo thorough training by a SKYLOTEC-certified instructor who is specifically trained on the device. User weight of up to 280 kg with pulley system; intuitive operation via rope guide and brake in the housing; lifting process via handwheel; with specialSEAL PAC <https://www.skylotec.com/eu-en/SEAL-PAC/P-SET-SEAL-PAC>s, an extended service life of up to 15 years can be guaranteed, which can even be doubled to 30 years on a one-time basis. For professional use, thoroughtraining <https://www.skylotec.com/eu_en/trainings/climbing-rescue-with-milan/> by SKYLOTEC-certified instructors who are specifically trained on the device is required.

FEATURES

Colour:	Black, Orange, White
Lifting function:	Yes
Max. abseiling height:	500 m
Max. load 1 person:	141.00 kg
Max. load 2 persons:	280.00 kg
Maximum lifetime:	20 years
Max. number of persons:	2
Maximum load:	280.00 kg
Minimum compatible rope diameter:	9.00 mm
Maximum compatible rope diameter:	9.00 mm
Max. Abseil speed:	0.90 m/s
Min. temperature:	-35 °C
Max. temperature:	60 °C
Panic function:	No
Rescue function:	Yes

MATERIAL

Material:	Aluminium, Steel, Polyamide

DATASHEET

MILAN 2.0 HUB