DATASHEET

# CLAW LINE CABLE 8MM D-BOLT CUSTOMIZED



## GENERAL

| | | | |
|---|---|---|---|
| Art.Nr: | CL-008-D-16,5 | Net weight: | 4.31 kg |
| GTIN: | 4030281299851 | Gross weight: | 4.31 kg |
| E-class number: | 40-02-01-90 | | |
| Customs tariff number: | 73121020 | | |

DATASHEET

# CLAW LINE CABLE 8MM D-BOLT CUSTOMIZED

Extremely durable, corrosion-resistant stainless steel cable with eyelet for fixed-installation vertical CLAW LINE arrester systems for use in combination with the single anchor point D-BOLT and the TOP POST as well as tested structural attachments. The CLAW LINE CABLE is an 8 mm stainless steel cable (V4A) in 7x7 construction. The upper end is firmly pressed onto a stainless steel thimble with a copper press sleeve on delivery. The rope length is determined individually. In combination with the tensioning device (CL-009), the CLAW LINE system offers a short end connection and thus a very comfortable entry area. An additional deflection of the steel rope at the lower end is not necessary due to the design of the system. This immensely reduces the risk of injury from open strands during installation and operation. Can only be used in conjunction with CLAW LINE shackle (CL-013).

## FEATURES

| | |
|---|---|
| Colour: | Silver |
| Maximum lifetime: | 10 years |
| Max. number of persons: | 3 |
| Min. temperature: | -30 °C |
| Max. temperature: | 80 °C |
| Rope access technique: | No |
| Vertical systems: | Vertical rope system |

## DIMENSIONS

| | |
|---|---|
| Rope length: | 16.50 m |
| Max height: | 0 mm |
| Min. height: | 0 mm |

## MATERIAL

| | |
|---|---|
| Material: | Stainless Steel |